

Distressed Glazed Porcelain

Betulla



TCRWD26B - 8" x 24"
TCRWD29B - 8" x 36"

Ciliegia



TCRWD26C - 8" x 24"
TCRWD29C - 8" x 36"

Noce



TCRWD26N - 8" x 24"
TCRWD29N - 8" x 36"

Sizes

Shape	Size	Sq Ft/Ctn	Pcs / Ctn
	8"x24" Field Tile (20 cm x 60 cm)	16.00	12
	8"x36" Field Tile (20 cm x 90 cm)	16.00	8

Technical Specifications


Description	Results	ASTM#
Water Absorption	≤ 0.50%	C373
PEI Rating	4	C1027
MOHS (Scratch Resistant)	6	MOHS
Frost Resistant	Unaffected	C1026
Breaking Strength	≥ 250 lbs	C648
Chemical Resistant	Unaffected	C650
DCOF Acutest	≥ 0.42	N/A

Product Information

Tile Thickness: 3/8"

Recommended Grout Joint: 3/16"

Shade Variation



Overlap should not exceed 33%

Icons PORCELAIN



Application

	Interior			Exterior	
	Residential	Light Commercial	Commercial	Residential	Commercial
Floors	•	•			
Walls / Backsplashes	•	•	•	•	•
Countertops	•	•	•	•	•
Showers	•	•	•	•	•
Pool Decking					
Pool Lining	•	•	•	•	•